

## Sartorius CP Model CPA8201



## Key features:

approx. 1.5 m

- Excellent, high-contrast, easy-to-read display, with especially large digits (16.5 mm)
- Built-in, motorized calibration weight. For the highest weighing accuracy at the touch of a key.
- isoCAL calibration and adjustment function. Through regular, fully automatic calibration, this function ensures that the balance's high level of accuracy remains constant
- Monolithic weigh cell technology rugged, precise, reliable – year after year
- Integrated mechanical components that effectively protect the weigh cell – from overloading or impact against the sides of the weighing pan.
- Rugged housing construction and use of housing materials that are highly resistant to chemicals – as a result, the balance can stand up to tough daily use

- RS-232C serial interface port
- Four digital filter levels allow the balance to be optimally adapted to the particular ambient conditions at the place of installation
- ISO/GLP-compliant logging of calibration, adjustment and weighing data using an optional data printer or a PC
- Very easy to operate; all keys feature positive click action; clear and logically arranged keypad
- Built-in application programs: counting, weighing in %, net-total formulation; animal weighing; mass unit conversion by toggling between 2 units
- Large weighing pan



Data printer



RS-232C/USB interface

Readability	0.1 g
Weighing capacity	8,200 g
Pan size	190x204 mm
Response time (avg.)	1 s
Housing (WxDxH)	213x342x88 mm
Reproducibility	<=± 0.1 g
Linearity	<=± 0.2 g

Key accessories	Order no.
Data printer with date, time and statistics functions	YDP03-0CE
RS-232C/USB interface cable, for connecting the balance to a PC with USB port; length	YCC01-USBM2